






REV	DESCRIPTION	APPD	DATE



P.C.B Holes Diagram

- 1.额定功率/Rating:DC 12V 50mA;
- 2.接触阻抗/Contact Resistance:100mΩ Max;
- 3.绝缘/Insulation Resistance:100MΩ Min;
- 4.耐电压/Withstanding Voltage:AC250V For 1 Minute;
- 5.寿命/Life:80,000 cycles Min;
- 6.动作力/Operating Force:250±50gf
- 7.行程/Travel:0.2±0.1mm



NO.	DESCRIPTION	QTY	MATERIAL	FINISH
1	STEM	1	PPA	BLACK
2	BASE	1	PPA	BLACK
3	CONTACT	1	SUS	PLATING Ag
4	TERMINAL	4	BRASS	PLATING Ag
5	COVER	1	SPCC	PLATING Sn

UNIT:MM  		SIZE: A4	SHEET: 1 OF 1	TITLE: TACT SWITCH
		SCALE: /	VER: 1	MODEL NO: TS44A-H11-M
PART NO:	DWG NO:			
GENERAL TOLERANCE: X.=±0.3, .X=±0.15 .XX=±0.1, .XXX=±0.05 .X*=±2° .XX*=±1°	DESIGNER BY:	DONY		
	APPROVED BY:	JACK		
	DATE:			
				 岡琦電子有限公司 GONGKIN ELECTRONIC CO.,LTD