




REV	DESCRIPTION	APPD	DATE



CIRCUIT DIAGRAM

P.C.B HOLES DIAGRAM

- 1.额定功率/Rating:DC 12V 50mA;
- 2.接触阻抗/Contact Resistance:100mΩMax;
- 3.绝缘/Insulation Resistance:100MΩMin;
- 4.耐电压/Withstanding Voltage:AC250V For 1 Minute
- 5.寿命/Life:100,000 cycler Min;
- 6.动作力/Operating Force:250±50gf
- 7.行程/Travel:0.2±0.1mm
- 8.使用温度/Operating Temperature:-20℃~70℃.

NO.	DESCRIPTION	QTY	MATERIAL	FINISH
1	STEM	1	PA66 or PPA	BLACK
2	BOTTOM	1	PA66 or PPA	BLACK
3	CONTACT	1	SUS	PLATING Ag
4	TERMINAL	2	C2680	PLATING SN
5	COVER	1	SPCC	PLATING Sn
UNIT:MM 		SIZE: A4	TITLE: TACT SWITCH	
		SHEET: 1 OF 1	MODEL NO: TS44A-VG45B-M	
		SCALE:  VER: 1		
PART NO:		DWG NO:		 岡琦電子有限公司 GONGKIN ELECTRONIC CO.,LTD
GENERAL TOLERANCE: X=±0.3, .X=±0.2 .XX=±0.1, .XXX=±0.05 .X*=±2° .XX*=±1°		DESIGNER BY:	DONY	
		APPROVED BY:	JACK	
		DATE:		